

BTM-MULTIFUNCTIONAL OILTEMPERATURE REGULATORS WITH INTEGRATED OILFILTER CONNECTION

TYPE LIST

Type	Max. flow rate m ³ /h	Thread	Insert	Specials
BTM Multifunctions oiltemperature control unit, 4-ways				
X1.438.55*)0.000.10	6	1/2"	X1.224.55.100	Standard
X1.439.55*)0.000.10	6	3/4"	X1.224.55.100	Standard
X1.438.71*)0.000.10	6	1/2"	X1.224.71.100	Standard
X1.439.71*)0.000.10	6	3/4"	X1.224.71.100	Standard
X1.306.71*)0.000.10	6	3/4"	X1.224.71.100	With optical service indicator for oilfilter
X1.307.71*)0.000.10	6	3/4"	X1.224.71.100	With electrical service indicator for oilfilter
X1.309.71*)0.000.10	6	3/4"	X1.224.71.100	Encl. electrical servicing indicator f. oilfilter, temp. switch on/off cooling fan at 80/75°C, oil sight glass/ check valve scavenging line
Oilfilter cartridge				
X1.300.00.165.10	6	3/4" UNF		
Adapter for oilfilter connection				
X1.300.00.002.10		M24 x 1,5, 3/4"		

*) = Please fill in requested start-to-open-temperature (°C): 25, 30, 35, 40, 45, 50, 55, 60, 65, 71, 79, 83, 87. Technical modifications reserved.